

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification⁶ : B04C 5/081, 9/00</p>	<p>A1</p>	<p>(11) International Publication Number: WO 97/28903 (43) International Publication Date: 14 August 1997 (14.08.97)</p>
<p>(21) International Application Number: PCT/GB97/00335 (22) International Filing Date: 6 February 1997 (06.02.97) (30) Priority Data: 9602631.5 9 February 1996 (09.02.96) GB (71) Applicant (for all designated States except US): BAKER HUGHES LIMITED [GB/GB]; Hammersley House, 2nd floor, 5-8 Warwick Street, London W1R 6JE (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): LLOYD, David, Douglas [GB/GB]; Bryher Cottage, Inglestone Common, Nr. Badminton, North Avon GL9 1BX (GB). THOMPSON, Peter, Austin [GB/GB]; 9 Mowberry Close, Longlevens, Gloucester GL2 0EN (GB). (74) Agent: GILL JENNINGS & EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).</p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).</p> <p>Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i></p>
<p>(54) Title: HYDROCYCLONE SEPARATOR</p> <div data-bbox="337 1129 1286 1369"></div> <p>(57) Abstract</p> <p>A dehydrating hydrocyclone having a cylindrical inlet portion (8) the length (l_1) of which is at least twice its diameter (d_1). The cylindrical portion leads into the tapered portion (9) the length (l_2) of which is at least twice the length (l_1) of the cylindrical portion. The tapered portion leads into a second cylindrical portion the length (l_3) of which is at least twice the length (l_1) of the first cylindrical portion. The cyclone may be used in a pressure vessel (11) in which any oil which flows through the underflow outlet of the hydrocyclone is allowed to settle under gravity within an underflow chamber (14) of the pressure vessel for removal separately from the water.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

HYDROCYCLONE SEPARATOR

The present invention relates to a hydrocyclone separator for separating a liquid mixture into a less dense component and a more dense component. The invention is particularly suitable for separating an oil/water mixture in which oil is the continuous phase and water is the dispersed phase. Such a hydrocyclone is known in the art as a dehydrating hydrocyclone.

In known dehydrating hydrocyclones, such as those disclosed in EP-A-259104 and EP-A-368849, the hydrocyclones have a separating chamber which, at the end adjacent to the inlet, has a short substantially cylindrical portion, followed by a first steeply tapering portion and a second less steeply tapering portion. The length of the cylindrical portion is short, so that the flow through the hydrocyclone quickly encounters the steeply tapering portion and is accelerated.

The dehydrating hydrocyclones operate effectively in as much as, for a given inlet oil concentration, a stream having a desired oil concentration can be obtained at the overflow outlet. However, this is done at the expense of the underflow outlet stream which represents an undesirably large proportion of the total flow, has a high oil concentration, and is still an oil continuous stream.

According to a first aspect of the present invention there is provided a hydrocyclone separator for separating a liquid mixture into a less dense component and a more dense component; the hydrocyclone having a wall defining an axially elongate separation chamber in the form of a surface of rotation, a liquid mixture inlet at one end of the chamber and which is arranged to cause the liquid mixture entering the separating chamber through the inlet to swirl about and progress along the axis, an overflow outlet at the one end for the less dense component, and an underflow outlet at the other end for the more dense component, the separation chamber comprising a first

substantially cylindrical portion extending axially from the one end towards the other end, and a tapered portion extending axially from the first substantially cylindrical portion towards the other end, wherein the length of the first cylindrical portion is at least twice its diameter.

Providing such a long cylindrical portion was previously believed to be undesirable as it leads to a deceleration of the flow. However, it has now been found that, contrary to expectations, such an arrangement actually improves the separation efficiency. The length of the cylindrical portion is preferably at least three times its diameter.

As the invention provides a more efficient separation, the same overflow oil concentration can be achieved at a lower underflow rate, so that the underflow stream represents a smaller proportion of the total flow and has a smaller concentration of oil, which can be made sufficiently small that the underflow stream is water continuous. This has advantages for subsequent separation of the underflow stream.

It is preferred that, within reason, the cylindrical portion should be as long as possible, and preferably the length of the first cylindrical portion should be at least n times the diameter of the first cylindrical portion, where n is any one of the integers from 3 to 20.

Preferably, the diameter of the first cylindrical portion is between 2.5 and 5 times the overflow outlet diameter, and is more preferably substantially 4 times the overflow outlet diameter.

Preferably, the length of the tapered portion is at least twice the length of the first substantially cylindrical portion.

Preferably, the included angle of the tapered portion is between 4° and 8° , and is more preferably substantially 6° .

In addition, separation can be improved if the separation chamber further comprises a second substantially

cylindrical portion extending from the tapered portion to the other end. The length of the second substantially cylindrical portion is preferably at least m times the diameter of the first cylindrical portion wherein m is any one of the integers from 2 to 20.

In order to improve the capacity of the hydrocyclone for a given size, the end wall at the one end is preferably inclined so that as the mixture from the inlet swirls about the axis of the chamber, the end wall imparts to the mixture an axial component of momentum in a direction towards the other end. Preferably, the end wall is substantially in the form of a helix which gradually extends axially towards the other end as the circumferential distance away from the inlet, or a respective inlet where more than one inlet is used, in the direction of swirl of the mixture increases and terminates in a step adjacent to the inlet, or the next inlet in the direction of swirl of the mixture where more than one inlet is used. This arrangement is the subject of co-pending British application GB 9516381.2.

In order to improve the quality of the overflow outlet stream, a core finder is preferably provided at the overflow outlet. This takes the form of a short tube extending axially from the overflow outlet into the separation chamber by a distance at least axially beyond the liquid mixture inlet, but not more than twice the axial length of the liquid mixture inlet.

The hydrocyclone separator in accordance with the invention has a particular application in a method of separating an oil/water mixture in which oil is the continuous phase, and water is the dispersed phase. The water content may be up to 20% by volume. In such a method, the mixture is introduced into the hydrocyclone inlet, and is separated into an oil enriched stream at the overflow outlet, and an oil depleted stream at the underflow outlet. Preferably, the oil depleted stream at the underflow outlet is water continuous.

According to a second aspect of the present invention there is provided an oil/water separation apparatus comprising a pressure vessel which is divided into an inlet chamber, an overflow outlet chamber and an underflow outlet chamber, the inlet chamber being provided with an inlet for an oil/water mixture, and at least one hydrocyclone, capable of separating a mixture of liquids into a more dense and a less dense component, with an inlet open to the inlet chamber, an overflow outlet for the less dense component and discharging into the overflow chamber, and an underflow outlet for the more dense component and discharging into the underflow chamber, the overflow chamber being provided with an oil outlet, and the underflow outlet chamber being provided with a water outlet and an oil outlet elevationally above the water outlet.

This apparatus provides what amounts to a two phase gravity separator for the liquid discharged from the underflow of the hydrocyclone(s). The apparatus is particularly useful when the or each hydrocyclone is a dehydrating hydrocyclone, as although the overflow stream is relatively pure oil, the underflow stream still contains a high proportion of oil. The apparatus is particularly successful when the or each hydrocyclone is a hydrocyclone separator according to the first aspect of the present invention, as the underflow from such hydrocyclone is coalesced and separates rapidly in the underflow chamber.

In order to promote phase separation in the underflow chamber, a baffle system is preferably provided in the upper part of the underflow chamber.

An example of a hydrocyclone separator constructed in accordance with the present invention will now be described with reference to the accompanying drawings, in which:

Fig. 1 is a schematic axial section of the hydrocyclone according to a first aspect of the present invention;

Fig. 2 is an enlarged section taken along line II-II in Fig. 1;

Fig. 3 is a section taken along line III-III in Fig. 2; and

Fig. 4 is a schematic drawing of the apparatus according to a second aspect of the present invention.

5 The hydrocyclone separator has a wall 1 defining a separation chamber 2. At one end of the separation chamber 2 are a pair of inlets 3 disposed symmetrically about the axis 4 of the hydrocyclone. As can be seen in Fig. 2 the inlets 3 are tangential to a circle centred on the axis 4, so that the liquid mixture entering the hydrocyclone is caused to swirl about the axis 4. The inlets, when viewed in the axial direction, converge towards the separation chamber at an angle of substantially 15° as shown in Fig. 2. The wall of the hydrocyclone adjacent to the inlet end is provided with two ramped surfaces 5 which are configured so that the liquid mixture entering the hydrocyclone is given an axial component of momentum by the surfaces 5 as it swirls about the axis 4.

15 An overflow outlet 6, having a diameter d_0 , is provided at the same end as the inlets 3, and an underflow outlet 7 is provided at the opposite end of the separation chamber 2.

20 The separation chamber is generally made up of three separate portions. The first portion is a cylindrical portion 8 of length l_1 and diameter d_1 which extends from the inlet end towards the opposite end. The cylindrical portion 8 extends without a discontinuity into a tapered portion 9 of length l_2 and having an included taper angle of θ . The tapered portion 8, in turn, extends without a discontinuity into a second cylindrical portion 10 of length l_3 and diameter d_3 . Typical values for these parameters are as follows:

25 $l_1 = 152\text{mm}$
 $d_1 = 40\text{mm}$
35 $d_0 = 10\text{mm}$
 $l_2 = 325\text{mm}$
 $\theta = 6^\circ$

$$l_3 = 250\text{mm}$$

$$d_3 = 6\text{mm}.$$

The separation apparatus shown in Fig. 4 comprises a pressure vessel 11 divided into an inlet chamber 12, an overflow chamber 13, and an underflow chamber 14 by a pair of plates 15. The inlet chamber 12 has a liquid mixture inlet 16 and a plurality of hydrocyclones 17, which are preferably in accordance with the first aspect of the present invention. The hydrocyclones 17 are held in place between the two plates 15 so that each hydrocyclone has its inlet open to the inlet chamber 12, its overflow outlet open to the overflow chamber 13, and its underflow outlet open to the underflow chamber 14.

An oil outlet 18 leads from the overflow chamber 13, and an optional pump 19 is provided to remove the oil. A second oil outlet 20 leads from the upper part of the underflow chamber 14 and is combined with the flow from the oil outlet 18. The flow of oil from the underflow chamber 14 is controlled, for example, by a differential pressure controller 21 in order to maintain the overall hydrocyclone split ratio at the desired level.

The water which settles at the bottom of the underflow chamber 14 is removed via a water outlet 22. The water flow is controlled, for example, by a valve 23 which responds to signals from an interface level control 24 to maintain the level of the oil/water interface in the underflow chamber 14 at a desired level.

A system of internal baffles 25 can be provided in the upper part of the underflow chamber 14 to promote phase separation.

CLAIMS

1. A dehydrating hydrocyclone separator for separating an oil/water mixture into a less dense oil enriched phase and a more dense oil depleted phase; the hydrocyclone having a wall (1) defining an axially elongate separation chamber (2) in the form of a surface of rotation, a liquid mixture inlet (3) at one end of the chamber and which is arranged to cause the liquid mixture entering the separating chamber through the inlet to swirl about and progress along the axis (4), an overflow outlet (6) at the one end for the less dense component, and an underflow outlet (7) at the other end for the more dense component, the separation chamber comprising an elongate first substantially cylindrical portion (8) extending axially from the one end towards the other end, and a tapered portion extending axially from the first substantially cylindrical portion (9) towards the other end, wherein the length (l_1) of the first cylindrical portion is at least twice its diameter (d_1).
2. A separator according to claim 1, wherein the length (l_1) of the cylindrical portion (8) is at least three times its diameter (d_1).
3. A separator according to claim 1, wherein the diameter (d_1) of the first cylindrical portion (8) is between 2.5 and 5 times the overflow outlet diameter (d_0).
4. A separator according to claim 1, wherein the length (l_2) of the tapered portion (9) is at least twice the length (l_1) of the first substantially cylindrical portion (8).
5. A separator according to claim 1, wherein the included angle (θ) of the tapered portion is between 4° and 8° .

6. A separator according to claim 1, wherein the separation chamber (2) further comprises a second substantially cylindrical portion (10) extending from the tapered portion (9) to the other end.

5

7. A separator according to claim 1, wherein the face of the end wall (5) at the one end is configured that as the mixture from the inlet swirls about the axis (4) of the chamber, the end wall imparts to the mixture an axial component of momentum in a direction towards the other end.

10

8. A separator according to claim 1, wherein a core finder is provided at the overflow outlet (6) comprising a short tube extending axially from the overflow outlet into the separation chamber by a distance at least axially beyond the liquid mixture inlet (6), but not more than twice the axial length of the liquid mixture inlet.

15

9. An oil/water separation apparatus comprising a pressure vessel (11) which is divided into an inlet chamber (12), an overflow outlet chamber (13) and an underflow outlet chamber (14), the inlet chamber being provided with an inlet (16) for an oil/water mixture, and at least one hydrocyclone (17), capable of separating a mixture of liquids into a more dense and a less dense component, with an inlet open to the inlet chamber, an overflow outlet for the less dense component and discharging into the overflow chamber, and an underflow outlet for the more dense component and discharging into the underflow chamber, the overflow chamber being provided with an oil outlet (18), and the underflow outlet chamber being provided with a water outlet (22) and an oil outlet (20) elevationally above the water outlet.

20

25

30

35

10. An apparatus according to claim 9, wherein a baffle system (25) is provided in the upper part of the underflow chamber (14).

1/2

Fig.1.




Fig.2.






Fig.3.



2/2

Fig.4.



INTERNATIONAL SEARCH REPORT

Inter. Appl. No.

PCT/GB 97/00335

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B04C5/081 B04C9/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 B04C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 230 210 A (AMOCO CORPORATION) 17 October 1990 see page 3, line 7 - line 24 see page 8, line 12 - line 17; figure 1	1,4-6,8
Y	---	3,7
Y	WO 89 08503 A (CONOCO SPECIALTY PRODUCTS INC.) 21 September 1989 see page 5, line 15 - page 9, line 1; figures	3
A	---	1,4,5,7
Y	GB 955 308 A (THE BAUER BROS. CO.) 15 April 1964 see page 2, line 29 - page 3, line 41; figures	7

	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *&* document member of the same patent family

Date of the actual completion of the international search

23 May 1997

Date of mailing of the international search report

06.06.97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Van der Zee, W

INTERNATIONAL SEARCH REPORT

Int. onal Application No

PCT/GB 97/00335

C/(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 068 809 A (NATIONAL RESEARCH DEVELOPMENT CORPORATION) 5 January 1983 see page 1, line 1 - page 2, line 8 see page 4, line 7 - page 5, line 30; figure	1,2,5,6
A	---	7
A	EP 0 259 104 A (THE BRITISH PETROLEUM COMPANY P.L.C. ET AL) 9 March 1988 cited in the application see the whole document	1,3-8
X	---	9,10
	US 2 341 087 A (DUNHAM) 8 February 1944 see page 1, right-hand column, line 9 - page 2, left-hand column, line 21; figures	
A	---	9,10
	US 4 778 494 A (PATTERSON) 18 October 1988 see column 3, line 42 - column 4, line 47; figures	
A	---	9
	WO 91 16117 A (CONOCO SPECIALTY PRODUCTS INC.) 31 October 1991 see page 5, line 20 - line 32; figure 1	
A	---	9
	WO 83 03369 A (TITECH) 13 October 1983 see abstract see page 3, line 27 - page 5, line 4; figure 1	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 97/00335

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2230210 A	17-10-90	US 4964994 A	23-10-90
		CA 1334510 A	21-02-95
		NO 175462 B	11-07-94
WO 8908503 A	21-09-89	US 5049277 A	17-09-91
GB 955308 A		US 3288300 A	29-11-66
EP 0068809 A	05-01-83	GB 2102310 A	02-02-83
		AU 559530 B	12-03-87
		AU 8471382 A	06-01-83
		CA 1191111 A	30-07-85
		GB 2102311 A,B	02-02-83
		JP 1655198 C	13-04-92
		JP 3014504 B	26-02-91
		JP 58030356 A	22-02-83
		US 4576724 A	18-03-86
		US 4722796 A	02-02-88
EP 0259104 A	09-03-88	AU 609053 B	26-04-91
		AU 7761087 A	03-03-88
		CA 1311445 A	15-12-92
		DE 3750671 D	24-11-94
		JP 63119862 A	24-05-88
		US 4749490 A	07-06-88
US 2341087 A	08-02-44	NONE	
US 4778494 A	18-10-88	NONE	
WO 9116117 A	31-10-91	NONE	
WO 8303369 A	13-10-83	EP 0105291 A	18-04-84
		GB 2128506 A	02-05-84
		JP 59500703 T	26-04-84
		SE 8306477 A	23-11-83